

784 45° UNION, GLOBALLY APPROVED, EXPLOSIVE ATMOSPHERE CABLE / CONDUIT ACCESSORY

- Allows the connection of conduit or glands to equipment
- Suitable for rigid or flexible conduit
- Integral coupling eliminates the need to rotate the conduit
- General purpose / industrial version available
- Equipment interface 'O' ring seal available
- 60°C to 200°C
- Globally marked, IECEx, ATEX & cCSAus



+200°C
↑
-60°C

Ex eb


Ex db

Ex ta

TECHNICAL CLASSIFICATION

DESIGN SPECIFICATION	BS 6121:Part 1:1989
ENCLOSURE PROTECTION	IK10 to IEC 62262 (20 joules) Brass & Stainless Steel only
INGRESS PROTECTION RATING**	IP66
AVAILABLE MATERIALS	Brass (standard), Electroless Nickel Plated Brass, Aluminium, Stainless Steel

** When CMP installation accessories are used. Refer to www.cmp-products.com for further information.



GLOBAL PRODUCT CERTIFICATION

ATEX CERTIFICATE	CML18ATEX1329U	IECEx CERTIFICATE	IECEx CML 18.0186U
CODE OF PROTECTION	Ⓜ II 2G 1D Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIC Da Ⓜ I M2 Ex db I Mb, Ex eb I Mb	CODE OF PROTECTION	Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIC Da, Ex db I Mb, Ex eb I Mb
COMPLIANCE STANDARDS	EN 60079-0,1,7,31	COMPLIANCE STANDARDS	IEC 60079-0,1,7,31
cCSAus CERTIFICATE (20S16-100)	1055233		
CODE OF PROTECTION	Class I, Div 1 & 2, Groups A,B,C,D; Enclosure type 4X: Class I, Zone 1, AEx de II; Ex de II		
COMPLIANCE STANDARDS	C22.2 No.0,0.5,30,94, CAN/CSA 60079-0,1,7, CAN/CSA E61241-1-1, UL Std 50, 1203, UL 60079-0,1,7		
EAC CERTIFICATE	TC RU C-GB.AA87.B.00487	RETIE APPROVAL	03866
NEPSI CERTIFICATE	GYJ18.1254U	INMETRO APPROVAL	TUV 12.1334U
MARINE APPROVALS	LRS: 01/00173	CCOE / PESO (INDIA) CERTIFICATE	P444949
UkrSEPRO	CLL 19.0370U	ECAS CERTIFICATE	20-02-05274

Male-to-Male thread option available.

Available with an equipment interface 'O' ring seal. For such options please add the suffix letter "R" after the type number in the ordering reference above, e.g. 784RDM2M2.

If 2 separate enclosures are required to be connected together please contact CMP Products.

PRODUCT SELECTION TABLE

METRIC				NPT				BORE DIAMETER "C"	MAX PROTRUSION LENGTH "D"	MAX OVERHANG LENGTH "F"	ACROSS FLATS HEX "G"	ACROSS CORNERS Ø "G"	INSTALLATION TORQUE (NM)
ORDERING REFERENCE (BRASS, METRIC)	MALE FORWARD THREAD SIZE "A"	MINIMUM THREAD LENGTH "E"	FEMALE REAR THREAD SIZE "B"	ORDERING REFERENCE (BRASS, NPT)	MALE FORWARD NPT THREAD SIZE "A"	MINIMUM NPT THREAD LENGTH "E" (IN)	FEMALE REAR THREAD SIZE "B"						
784DM2M2	M20 X 1.5	15.0	M20 X 1.5	784DT1T1	½"	0.79	½"	14.3	60.6	55.8	46.0	50.6	7
784DM3M3	M25 X 1.5	15.0	M25 X 1.5	784DT2T2	¾"	0.80	¾"	20.1	65.9	61.2	50.0	55.0	10
784DM4M4	M32 X 1.5	15.0	M32 X 1.5	784DT3T3	1"	0.98	1"	26.4	69.3	69.7	60.0	66.0	15
784DM5M5	M40 X 1.5	15.0	M40 X 1.5	784DT4T4	1¼"	1.01	1¼"	32.6	74.9	76.4	65.0	71.5	25
784DM6M6	M50 X 1.5	15.0	M50 X 1.5	784DT5T5	1½"	1.03	1½"	43.0	93.5	87.9	75.0	82.5	30
784DM7M7	M63 X 1.5	15.0	M63 X 1.5	784DT6T6	2"	1.06	2"	53.0	102.7	102.8	90.2	99.2	45

All dimensions shown are in millimetres unless otherwise stated

For material options please add the following suffix to the Ordering Reference; Brass (no suffix required), Nickel Plated Brass "5", 316 Grade Stainless Steel "4", Copper Free Aluminium "1"